



Overview

TX7331 Intelligent Graphic Repeater Panel is designed with built-in MCU processor and it can fast relay response with simultaneous audible and visual signal output. This repeater panel can also program to limit the zone display from All Zones into a particular zone or device. Also it can supervise and indicate the groups as well as device. The unit is connected through the communication loop of TX7004 Intelligent control panel along with the devices and can install up to 254 units per loop. The repeater panel can be used whenever there is a need to relay information to multipoint informing key personnel. The unit is compact size and aesthetically pleasing with unobtrusive design that will complement modern building designs. The unit is compatible to the TX7004 Analogue Intelligent Fire Alarm Control Panel, produced by single manufacture T&A, to avoid addressable communication compatibility problem.

TX7331

Mimic Panel

Features and Benefits

- Alarm LED display of individual device or a zone and group
- Send sound alarm signal with the control panel
- Can display up to 256 alarm points.
- Can upload default information
- Fully Monitored with Self-test function
- Assemble kit with LED's, Cabinet is optional

Technical Specification

Power Rating	
Power Supply	DC-24V (External EN54-4 PSU is required) Recommended PSU is TX24-5A/10A
Bus Voltage	16V-28V
Bus Current	1.0mA
Bus Alarm Current	1.2mA
Standby Current	25mA
Alarm Current	80mA
Indicator	LED Display
Material / Colour	Flat sheet Metal / Light Gray (Optional)
Dimension	349mm x 275mm x 68mm (Standard)
IP Grade	IP30
Operating Environment	
Temperature	-10°C~+50°C
Relative Humidity	≤95%, non-condensing