

# EPS10-1 and EPS10-2 Alarm Pressure Switches

System Sensor EPS10 Series switches are designed for use in wet, dry, deluge, and pre-action automatic sprinkler systems to indicate a discharge from a sprinkler.



#### **Features**

- · Sensitivity adjustment wheel, no special tools required
- · Reinforced diaphragm resists pressure spikes
- Two conduit entrances
- Both one- and two-switch models available

The EPS10-1 has a single SPDT switch while the EPS10-2 model contains two SPDT switches. The EPS10 Series features field adjustable pressure sensitivity to provide an alarm response between 4 and 20 psi. It is factory set to respond at 4 – 8 psi on rising or falling pressure. The pressure adjustment wheel requires no special tools and does not affect switch synchronization on the EPS10-2. The EPS10 Series switches are NEMA 4 rated.

## **Agency Listings**













# Specifications, EPS10-1 and EPS10-2


#### Architectural/Engineering Specifications EPS10-1 (SPDT), EPS10-2 (2/SPDT)

Model shall be an EPS10-1 or EPS10-2 pressure type waterflow switch as manufactured by System Sensor of St. Charles, IL. They shall be installed on the sprinkler system with connection as shown on the drawings and/or as specified herein. Pressure switches shall be of the bellows-activated type. Switches shall have a maximum service pressure rating of 300 psi and shall be factory adjusted to operate at a pressure of 4 – 8 psi. There shall be one (1) or two (2) SPDT contacts rated at 10.0 Amp @ 125/250 VAC and 2.5 Amp @ 6/12/24 VDC. The contractor shall furnish and install, where indicated on the plans, pressure switches according to appropriate NFPA standards. Switches shall be provided with a ½″ NPT male pressure connection to be connected to the alarm check valve of a "wet" sprinkler system, into the intermediate chamber of a "dry" system, or to a pre-action or deluge valve. They shall be activated by any flow of water equal to or in excess of the discharge from one sprinkler head. Switches shall provide 1 knockout type and 1 open hole for ½″ conduit fitting attachment and a ground screw provision for electrical grounding. The switch enclosure shall be weatherproof and carry a UL 4x/NEMA 4 rating when used with proper electrical fittings and conduit. The cover shall incorporate tamper-resistant screws. The unit shall be listed by Underwriters Laboratories, Inc. and approved by Factory Mutual.


#### Specifications, EPS10-1 and EPS10-2 (continued)

Physical/Operating Spe			
Maximum Operating	300 psi	Operating Temperature	Indoor or outdoor use:
Pressure		Range	–40°F to 160°F (–40°C to 71°C)
<b>Maximum Adjustment</b>	4 to 20 psi	Cover Tamper Switch	UL Models: Optional P/N 546-8000
Pressure Range			ULC Models: Factory Installed
Differential	Approximately 3 psi throughout range	Enclosure	Rated UL 4x, NEMA 4 for indoor or
			outdoor use
Factory Setting	Operates at rising pressure 4 to 8 psi	Shipping Weight	1.2 lbs. (.54 Kg)
Switch Contact	EPS10-1: One set SPDT (Form C)	Service Use	Automatic Sprinkler: NFPA 13
Ratings	EPS10-2: Two sets SPDT (Form C)		One or Two Family Dwelling: NFPA 13D
	10.0 A, ½ HP @ 125/250 VAC		Residential Occupancies up to 4 Stories:
	2.5 A @ 6/12/24 VDC		NFPA 13R
			National Fire Alarm Code: NFPA 72
<b>Pressure Connection</b>	½"NPT male glass reinforced nylon	Warranty	3 years
Dimensions	5.12"H × 3.325"W × 4.250"L		
	$(13.0 \text{ cm} \times 8.4 \text{ cm} \times 10.8 \text{ cm})$		


### **Typical Sprinkler Applications**




#### **Pressure Switch Basic Dimensions**



#### **Electrical Connections**





# **Ordering Information**

Part No.	Description	
EPS10-1	Alarm Waterflow Pressure Switch, One SPDT, 4–20 PSI	
EPS10-2	Alarm Waterflow Pressure Switch, Two SPDT, 4–20 PSI	
EPSA10-1	ULC/Canadian Version	
EPSA10-2	ULC/Canadian Version	
Replacement Parts		
S07-66-02	Replacement Tamper Screws for Cover of EPS	
WFDW	Replacement Tamper Proof Wrench for Cover of EPS	
546-8000	Cover Tamper Switch for EPS Series	

